



ELECTRICAL SPECIFICATIONS

Frequency Range	120 ~ 6,000	MHz
Coupling Tolerance	20 ± 3.50	dB, nom'l.
Flatness (Sensitivity)	± 2.00	dB, max.
Directionality	18	dB, min. (to 2.7GHz)
	12	dB, min. (2.7~6GHz)
Main Line Insertion Loss	1.0	dB, max.
Main Line VSWR	1.4	:1, max.
Coupled Port VSWR	1.4	:1, max.
Forward Average Power	100	Watts, max.
Reverse Average Power	50	Watts, max.
Impedance	50	Ohms, nom'l.
Peak Power	UNSPEC'D.	kW, max (1μs, 2% duty)
Passive Intermodulation	-150 dBc	2x +43 dBm, nom'l.

MECHANICAL SPECIFICATIONS

R.F. Interface	N Female
Operating Temperature	-40 ~ +85 °C (Tested at +25°C)
Environment	Indoor use only.
Humidity	90%, Non-Condensing
Weight	1.6 lb. Nom'l.

WERBEL MICROWAVE

622 State Hwy. 10 West, Unit 9, Whippany, New Jersey, 07981
 Sales@WerbelMicrowave.com

Tel. (973) 515-3001 ~ FAX (973) 515-3004
 http://www.WerbelMicrowave.com CAGE Code: 78YZ0

2CN1206-20

Dual Directional Coupler

Connectors	Brass, Succoplate
Contact Pins	Beryllium Copper, Gold Plate
Insulators	PTFE
Housing	Aluminum, RoHS Chemical Conversion
Finish	Optional / Specify

REV	DESCRIPTION	ENG.	DATE
1	ECN 1095	ETW	2/12/2017

Input power is rated for load VSWR of 1.20:1, max. Insertion loss excludes coupling/split loss.
 All dimensions in inches with tolerance ± .010" and are typical unless otherwise specified.
 Specifications are subject to change without notice. This document shall not form part of any contract.