



ELECTRICAL SPECIFICATIONS

Frequency Range	0.5 ~ 6.0	GHz
Amplitude Balance	0.3	dB, max.
Phase Balance	2	degrees, max.
Isolation	18	dB, min.
Insertion Loss	1.0	dB, max.
Common Port VSWR	1.6	:1, max.
Split Port VSWR	1.4	:1, max.
Average Power as Splitter	30	Watts, max.
Average Power as Combiner	0.5	Watts/port, max.
Impedance	50	Ohms, nom'l.
Peak Power	UNSPEC'D.	kW, max (2% duty)
Passive Intermodulation	UNSPEC'D.	2x +43 dBm, nom'l.

MECHANICAL SPECIFICATIONS

R.F. Interface	SMA Female
Operating Temperature	-40 ~ +65 °C (Tested at +25 °C)
Environment	Indoor use only.
Humidity	90%, non-condensing.
Weight	6.3 oz Nominal

WERBEL MICROWAVE

622 State Hwy. 10 West, Unit 9, Whippany, New Jersey, 07981
 Sales@WerbelMicrowave.com

Tel. (973) 515-3001 ~ FAX (973) 515-3004
 http://www.WerbelMicrowave.com CAGE Code: 78YZ0

2PSX506

Connectors	Brass, Gold Plate
Contact Pins	Beryllium Copper, Gold Plate
Insulators	PTFE
Housing	Aluminum, RoHS Chemical Conversion
Finish	Optional / Specify

Power Splitter / Combiner

REV	DESCRIPTION	ENG.	DATE
0	Engineering release.	ETW	1/21/2017

Input power is rated for load VSWR of 1.20:1, max. Insertion loss excludes coupling/split loss.
 All dimensions in inches with tolerance $\pm .010"$ and are typical unless otherwise specified.
 Specifications are subject to change without notice. This document shall not form part of any contract.